# RJ-45 Surface Mount Box - 2 Port

**erat**



## Features

- Suitable for installation UTP-FTP Keystone Jack
- Label area for giving name or number to sockets
- Compatible with all standard cable carrier equipment
- Provides accurate positioning with claw mounting mechanism.
- Sytimax Jack Compatible (option)
- Panduit Jack CJ688TGIW compatible module (optional)
- Supports Cat5, Cat6, Cat7 cables (supports between 10 Dec - 1200 MHz)
- White color, RAL 9010
- Slot entry design with a 40° angle to avoid damage to the cable attached to the slot in case of bending
- Plug plug-out: 750 times
- LSZH

Glazed label area with quality materials, stylish design and standard jack module, all standard to the module carrier, which fits seamlessly with the keystone faceplates of the brands.

## BENEFITS

- Universal mounting Standard
- Low voltage effect
- Carrier channels for trouble-free use in all facilities
- Does not need any additional mounting brackets October
- In the office or in places where there is regular use and stylish appearance

## TECHNICAL SPECIFICATIONS

| Color | White (RAL9010) |
|---|---|
| Flammability | UL 94 Classification 1.5/3 ,0/ 6.0mm sample |
| Flammability | Heat Deflection Temperature18.56 kgf /cm   ASTM D648     F (C ) 169 ( 76 )<br>VICAT Softening Temperature :   5kg         ISO R 306      F (C ) 187 ( 86 ) |

## ORDERING INFORMATION

| Definition | Minimum Order | Package Details |
|---|---|---|
| RJ45 Surface Mounted Socket Model White | 50 pcs | 1 package 50 pcs |

| PACKAGE DIMENSIONS (Plastic Bag) | PACKAGE DIMENSIONS (Carton Box) |
|---|---|
| Width : 150mm<br>Height : 180mm<br>Depth : 70mm | Width : 250mm<br>Height : 250mm<br>Depth : 70mm |

*The technical data and dimensions in the table above may vary.