



CAT 6 F-UTP 24 AWG Outdoor Data Cable



WHERE IT IS USED/ FEATURES	CABLE STRUCTURE
<p>ERAT CAT 6 Outdoor UV resistant, black PE Outer Jacket cables are suitable for harsh conditions for external applications. Used to transport digital, analog voice, data, video and POE signals.</p> <p>ERAT CAT 6 F/UTP cables, 250 MHz cable carrying data at 1 Gbps/sec is the type. To minimize the interaction of cable pairs, It is sheathed using a separator. HFFR or different according to customer demand Outer Jacket production is carried out in different specifications.</p> <ul style="list-style-type: none"> • 1000BASE-TX Gigabit Ethernet • 1000BASE-T Gigabit Ethernet • ATM 155 / ATM 25 • 100BASE-T "Fast Ethernet" • 100BASE-T2/ 100BASE-T4 • 100BASE-TX • 10BASE-T Ethernet • ISDN, TPDDI, TP-PMD • Power Over Ethernet (PoE) 	<ol style="list-style-type: none"> 1. Copper Conductor 2. PE Insulation 3. Ground Wire 4. Separator 5. Polyester Tape 6. Aluminium Foil 7. Outer Jacket

PHYSICAL PROPERTIES

Conductive	Solid, annealed copper
Conductor Diameter	24 AWG
Insulation	Polyolefin
Number of Insulated Conductors	8, twisted in 4 pairs
Polyester Tape Wrap	Polyester Tape provides 100% coverage
Ground Wire	Solid, tin-coated annealed copper
Overall Inner Shield	Laminated aluminum foil providing 100% coverage (foil face is introverted)
Outer Jacket	Resistant to outdoor conditions, fully compatible with PE Th and UV conditions
Jacket Color	Black. (Different colors can be produced according to customer demand.)
Cable information the text	Brand, Type of cable, Relevant standards, Date, Serial number, Meter

MECHANICAL AND ENVIRONMENTAL PROPERTIES

Pulling Force	60 N / mm ² max
Bending Radius (Short Term)	4 x Cable Diameter
Bending Radius (Long Term)	8 x Cable Diameter
Operating Temperature	-40 to +80 °C
Installation Temperature	-10 to +60 °C
Storage Temperature	-40 to +80 °C

CAT 6 F-UTP 24 AWG Outdoor Data Cable

PACKAGING & SIZE & WEIGHT		
Packaging Type	Outer Diameter (mm)	Approximate Weight (kg)
500 m Plywood Reel	7.5±0.3	21
1000 m Plywood Reel	7.5±0.3	43

ELECTRICAL SPECIFICATIONS	
Characteristic Impedance	100±6 Ohm @ 1-250 MHz
DC Resistance	93 Ohm/km max.
Resistance Unbalance	2% max.
Capacitance	45 pF/m nom. @ 1 KHz
Capacity Imbalance (Wire to ground)	1600 pF/km max. @ 1 KHz.
Voltage	72 Vdc max.
Dielectric Strength	1.7 kV a.c. / 2 seconds
Velocity of Propagation (NVP)	Min. % 67 - 69
The Signal Transmission Time (Prop. Delay)	534 + 36/f ^{1/2} nS/100m max @ 1-250 MHz
Propagation Delay Skew	45 nS/100m max @ 1-250 MHz
Insulation Resistance	5000 MegaOhm·km min. @ 500 Vdc
Coupling attenuation	55 dB min @ 30-100 MHz 55-20Log(f/100) @100-250 MHz
Transfer Impedance	10 mOhm/m max @ 1-10 MHz 30 mOhm/m max @ 30 MHz

Frequency (MHz)	Return Loss (dB)	Insertion Loss (dB)	NEXT Loss (dB)	PS NEXT Loss (dB)	ACRF (dB)
	Min.	Max.	Min.	Min.	Min.
1.00	19.1	1.9	65.0	62.0	64.2
4.00	21.0	3.5	64.1	61.8	52.1
8.00	21.0	5.0	59.4	57.0	46.1
10.00	21.0	5.5	57.8	55.5	44.2
16.00	20.0	7.0	54.6	52.2	40.1
20.00	19.5	7.9	53.1	50.7	38.2
25.00	19.0	8.9	51.5	49.1	36.2
31.25	18.5	10.0	50.0	47.5	34.3
62.50	16.0	14.4	45.1	42.7	28.3
100.00	14.0	18.6	41.8	39.3	24.2
200.00	11.0	27.4	36.9	34.3	18.2
250.00	10.0	31.1	35.3	32.7	16.2

ISOLATED COLORS							
Blue	Blue/White	Orange	Orange /White	Green	Green /White	Brown	Brown/White