



## CAT 6 U-FTP 23 AWG OUTDOOR DATA CABLE



WHERE IT IS USED/ FEATURES	CABLE STRUCTURE
<p>ERAT CAT 6 Outdoor UV resistant, black PE sheathed cables, external Suitable for applications in severe conditions. Digital, analog voice, data, video and POE It is used to carry signals.</p> <p>ERAT CAT 6 U/FTP cables, cable carrying data at 250 MHz 1 Gbps/sec is the type. Outer sheath production with HFFR or different features according to customer demand is being done.</p> <ul style="list-style-type: none"> <li>• 1000BASE-TX Gigabit Ethernet</li> <li>• 1000BASE-T Gigabit Ethernet</li> <li>• ATM 155 / ATM 25</li> <li>• 100BASE-T "Fast Ethernet"</li> <li>• 100BASE-T2/ 100BASE-T4</li> <li>• 100BASE-TX</li> <li>• 10BASE-T Ethernet</li> <li>• ISDN, TPDDI, TP-PMD</li> <li>• Power Over Ethernet (PoE)</li> </ul>	<ol style="list-style-type: none"> <li>1. Copper Conductor</li> <li>2. PE Insulation</li> <li>3. Ground Wire</li> <li>4. Aluminium Foil</li> <li>5. Outer Jacket</li> </ol>

PHYSICAL PROPERTIES	
<b>Conductive</b>	Solid, annealed copper
<b>Conductor Diameter</b>	23 AWG
<b>Insulation</b>	Polyolefin
<b>Number of Insulated Conductors</b>	8, twisted in 4 pairs
<b>Ground Wire</b>	Solid, tin-coated annealed copper
<b>Individual Pair Shield</b>	Laminated aluminum foil providing 100% coverage (the foil face is turned outwards)
<b>Outer Jacket</b>	Resistant to outdoor conditions, fully compatible with PE Th and UV conditions
<b>Jacket Color</b>	Black. (Different colors can be produced according to customer demand.)
<b>Cable information the text</b>	Brand, Type of cable, Relevant standards, Date, Serial number, Meter

MECHANICAL AND ENVIRONMENTAL PROPERTIES	
<b>Pulling Force</b>	60 N / mm <sup>2</sup> max
<b>Bending Radius (Short Term)</b>	4 x Cable Diameter
<b>Bending Radius (Long Term)</b>	8 x Cable Diameter
<b>Operating Temperature</b>	-40 to +80 °C
<b>Installation Temperature</b>	-10 to +60 °C
<b>Storage Temperature</b>	-40 to +80 °C

## CAT 6 U-FTP 23 AWG OUTDOOR DATA CABLE

PACKAGING & SIZE & WEIGHT		
Packaging Type	Outer Diameter (mm)	Approximate Weight (kg)
500 m Plywood Reel	7.1±0.3	23.3
1000 m Plywood Reel	7.1±0.3	46.2

ELECTRICAL SPECIFICATIONS	
Characteristic Impedance	100±6 Ohm @ 1-250 MHz
DC Resistance	93 Ohm/km max.
Resistance Unbalance	2% max.
Capacitance	45 pF/m nom. @ 1 KHz
Capacity Imbalance (Wire to ground)	1600 pF/km max. @ 1 KHz.
Voltage	72 Vdc max.
Dielectric Strength	1.7 kV a.c. / 2 seconds
Velocity of Propagation (NVP)	Min. % 78 - 80
The Signal Transmission Time (Prop. Delay)	534 + 36/f <sup>1/2</sup> nS/100m max @ 1-250 MHz
Propagation Delay Skew	45 nS/100m max @ 1-250 MHz
Insulation Resistance	5000 MegaOhm-km min. @ 500 Vdc
Coupling attenuation	55 dB min @ 30-100 MHz 55-20Log(f/100) @100-250 MHz
Transfer Impedance	10 mOhm/m max @ 1-10 MHz 30 mOhm/m max @ 30 MHz

Frequency (MHz)	Return Loss (dB)	Insertion Loss (dB)	NEXT Loss (dB)	PS NEXT Loss (dB)	ACRF (dB)
	Min.	Max.	Min.	Min.	Min.
1.00	19.1	1.9	65.0	62.0	64.2
4.00	21.0	3.5	64.1	61.8	52.1
8.00	21.0	5.0	59.4	57.0	46.1
10.00	21.0	5.5	57.8	55.5	44.2
16.00	20.0	7.0	54.6	52.2	40.1
20.00	19.5	7.9	53.1	50.7	38.2
25.00	19.0	8.9	51.5	49.1	36.2
31.25	18.5	10.0	50.0	47.5	34.3
62.50	16.0	14.4	45.1	42.7	28.3
100.00	14.0	18.6	41.8	39.3	24.2
200.00	11.0	27.4	36.9	34.3	18.2
250.00	10.0	31.1	35.3	32.7	16.2

ISOLATED COLORS							
Blue	White	Orange	White	Green	White	Brown	White