


CAT 7A S-FTP 22 AWG 1000 MHZ DATA CABLE



WHERE IT IS USED/ FEATURES	CABLE STRUCTURE
<p>ERAT CAT 7A kabloları dijital ve analog ses, veri ve video, POE sinyallerinin taşınmasında kullanılır</p> <p>ERAT CAT 7A S/FTP kabloları, 10000 Megabit 1000 MHz hızında veri taşıyan kablo türüdür. Müşteri taleplerine göre LSZH-HFFR ve PVC kılıflı olarak üretim yapılmaktadır.</p> <ul style="list-style-type: none"> • 10000BASE-TX Gigabit Ethernet • 10000BASE-T Gigabit Ethernet • 1000BASE-TX Gigabit Ethernet • 1000BASE-T Gigabit Ethernet • ATM 155 / ATM 25 • 100BASE-T "Fast Ethernet" • 100BASE-T2/ 100BASE-T4 • 100BASE-TX • 10BASE-T Ethernet • ISDN, TPDDI, TP-PMD • Power Over Ethernet (PoE) 	<ol style="list-style-type: none"> 1. Copper Conductor 2. PE Insulation 3. Aluminium Foil 4. Tinned Copper Braid 5. Outer Jacket

PHYSICAL PROPERTIES	
Conductive	Solid, annealed copper
Conductor Diameter	22 AWG
Insulation	Polyolefin
Number of Insulated Conductors	8, twisted in 4 pairs
Overall Inner Shield	Laminated aluminum foil providing 100% coverage (the foil face is turned outwards)
Overall Outer Shield	Tinned Copper Braid
Outer Jacket	LSZH (Low Smoke Zero Halogen) flame retardant or PVC component
Jacket Color	Gray. (Ral 7040) (Different colors can be produced according to customer demand.)
Cable information the text	Brand, Type of cable, Relevant standards, Date, Serial number, Meter
CPR	Dca









MECHANICAL AND ENVIRONMENTAL PROPERTIES	
Pulling Force	50 N / mm ² max
Bending Radius (Short Term)	4 x Cable Diameter
Bending Radius (Long Term)	8 x Cable Diameter
Operating Temperature	-40 to +70 °C
Installation Temperature	-10 to +50 °C
Storage Temperature	-40 to +70 °C

CAT 7A S-FTP 22 AWG 1000 MHZ DATA CABLE

PACKAGING & SIZE & WEIGHT		
Packaging Type	Outer Diameter (mm)	Approximate Weight (kg)
500 m Plywood Reel	7.9±0.3	32.3
1000 m Plywood Reel	7.9±0.3	64.2

ELECTRICAL SPECIFICATIONS	
Characteristic Impedance	100±6 Ohm @ 1-1000 MHz
DC Resistance	70 Ohm/km max.
Resistance Unbalance	2% max.
Capacitance	45 pF/m nom. @ 1 KHz
Capacity Imbalance (Wire to ground)	1600 pF/km max. @ 1 KHz.
Voltage	72 Vdc max.
Dielectric Strength	1500 Volt / 1 dakika min. rms
Velocity of Propagation (NVP)	Min. %77 - 80
The Signal Transmission Time (Prop. Delay)	534 + 36/f ^{1/2} nS/100m max. @ 1-1000 MHz
Propagation Delay Skew	25 nS/100m max @ 1-1000 MHz
Insulation Resistance	5000 MegaOhm·km min. @ 500 Vdc
Coupling attenuation	55 dB min @ 30-100 MHz 55-20Log(f/100) @100-1000 MHz
Transfer Impedance	10 mOhm/m max @ 1-30 MHz 30 MOhm/m max @ 30-100 MHz

Frequency (MHz)	Return Loss (dB)	Insertion Loss (dB/100m)	NEXT Loss (dB)	PS NEXT Loss (dB)	PS ELFEXT (dB/100m)
1	20,0	2,1	78,0	75,0	-
4	23,0	3,7	78,0	75,0	75,0
8	24,5	5,2	78,0	75,0	74,2
10	25,0	5,8	78,0	75,0	72,3
16	25,0	7,3	78,0	75,0	68,2
20	25,0	8,2	78,0	75,0	66,3
25	24,3	9,2	78,0	75,0	64,3
31,25	23,6	10,3	78,0	75,0	62,4
62,5	21,5	14,6	78,0	75,0	56,4
100	20,1	18,5	75,4	72,4	52,3
200	18,0	26,5	70,9	67,9	46,3
250	17,3	29,7	69,4	66,4	44,3
300	17,3	32,7	68,2	65,2	42,8
400	17,3	38,0	66,4	63,4	40,3
500	17,3	42,8	64,9	61,9	38,3
600	17,3	47,1	63,7	60,7	36,7
1000	17,3	61,9	60,4	57,4	32,3

ISOLATED COLORS							
							
Blue	White	Orange	White	Green	White	Brown	White