

Fiber Optic Splice Box TYPE-1




Applications

- High chemical resistant construction.
- Locked cassette system provides ease of installation.
- High quality, waterproof, reusable.
- Suitable for SM and Ribbon cable splices.
- 8 port cable entries are available for GPON and FTTx applications.
- Thanks to its product dimensions, it provides ease of application even in the smallest manholes.
- There is an additional silicone protective housing that prevents jamming.
- Provides comfortable routing of fibers in the cassette in multiple buffer inputs.

Applications

- In manhole, overhead and direct burial.
- Fiber optic intermediate distribution points.
- Building and campus network applications.



PARAMETERS

PARAMETERS		TYPE-1
Dimensions	480mm/ Diameter: 160mm	
Cable entry ports	8	
Max. B Port Diameter	25.00mm	
Max. Oval 1 Diameter	65.00mm Min. 8mm / Max. 25mm	
Max. Oval 2 Diameter	50.50mm Min. 8mm / Max. 18mm	
Cassette Capacity	12/24 core	
Cassette Count	6 Cassette	
Splice Capacity	4 / 12 / 24 / 36 / 48 / 60 / 72 / 96 / 144 core	
Center Element Fixing Place	Galvanized Stainless Steel / FRB	
Cable Reserve Slot	2 buffered fiber optic cable with 6 buffers. (Cable varies according to the number of buffers.)	