

Fiber Ethernet Media Converter MM



1 10/100/1000 mm



1 port 10/100/1000Base-Tx to 1000Base-Fx SC Fiber Media Converter

Specifications

Product Name	10/100/1000Mbps Media converter (Dual fiber multi mode)
Model	11GE-SC2
Interface	RJ-45: 1×10/100/1000Base-TX Fiber: 1×1000Base-FX Fiber Connector: SC/FC/ST Dual fiber Multi Mode
Compliant Standards	IEEE 802.3, 10BASE-T IEEE 802.3u, 100BASE-TX IEEE 802.3u, 100BASE-FX IEEE 802.3x, Flow Control
Optical Cable	UTP: cat.5/cat.6 (Max Distance 100m) Fiber(Multi Mode): 8/125,8.7/125,9/125,10/12
Transmission Distance	UTP: 100m-150m Fiber: – Multi Mode 2km – Single Mode 2km/40km/60km/80km/100km
Flow Control	Full-duplex IEEE802.3x Flow Control Half-duplex backpressure flow control
Power	DC5V
Power Consumption	< 5 watts
Working Environment	Environment temperature:-20°C 60° Storage temperature: -30 °70 ° Operating Humidity: 5%-95% (No-condensing) Storage Humidity: 5%-95% (No-condensing)
Dimensions(W×D×H)	110mm×70mm×25mm
Weight	0.3kg/piece